Cat.No.6418-00

Pocket Type Digital pH Meter Model SK-631PH



Features

- Compact, pocket-size
- Three point calibration is available at pH1.01, pH6.86 and 10.01pH for accurate measurement
- Auto power-off function, HOLD function
- Auto temperature compensation
- Waterproofness (IPX4 grade of JIS C 0920)

Specifications

Cat. No.		6416-00	6418-00	6420-00
Model		SK-630PH	SK-631PH	SK-632PH
Measuring range	pH	2.0 to 12.0pH	2.0 to 12.0pH	2.0 to 12.0pH
	°C	-	0.0 to 50.0°C	0.0 to 50.0°C
Accuracy	pH	±0.6pH	±0.5pH	±0.4pH
	°C	-	±0.1°C	±05°C
Resolution	pH	0.1pH	0.1pH	0.01pH
	°C	-	0.5°C	0.1°C
Elements	pH	Glass electrode	Glass electrode	Glass electrode
	°C	-	Thermistor	Thermistor
Measuring ambient		0 to 50°C		
Power requirement		Alkaline Batteries LR44(GPS76E) x 4 pcs.		
Battery life		About 20 hours continuous		
Materials		Case : ABS resin Sensor : Glass		
Dimensions		(W)36 x (H)150 x (D)25mm		

Weight	About 65g (inclusive of batteries)
Functions	Calibration function, Auto temperature compensation(*1) HOLD. Auto power-Off, (possible to cancel the auto power-off)
Waterproof property	JIS C 0920 IPX4
Standard accessories	Instruction manual, Alkaline battery LR44(GPS76E) x 4 pcs: Factory set- Alkaline battery LR44(GPS76E) x 4 pcs

*1. Not applicable for the model SK-630PH