

Cat.No.8091-50

Temperature/humidity Indicator Model SK-M460-TRH

Model

SK-M460-TRH



Digital indicator for temperature and humidity with the LED (height of character 57mm). Input: 0 to 1VDC
Temperature/humidity transmitter model SK-RHC-V (output: 0 to 1VDC) can connect with this indicator.

Features

- *Digital indicator which displays temperature and humidity simultaneously with LED (height of character: 57mm)
- *Input: 0 to 1VDC
- *Temperature/humidity transmitter Model SK-RHC-V (output 0 to 1VDC) can connect with. (built-in the Power supply for SK-RHC-V)
- *Wall-mount type and possible to attach hanging hooks at option
- *Alarm function (upper/lower limits) is available for ordering
- *Buzzer and rotating warning light can connect with.

Specifications

Display	7 segment LED height of character: approx. 57mm
Display range	Temperature: 0.0 to 65.0 °C Humidity: 5.0 to 99.9%rh Display accuracy: $\pm(0.3 + 1 \text{ digit})^{\circ}\text{C}/\%rh$
Input	Temperature: 0 to 650mVDC (0.0 to 65.0 °C) Humidity : 50 to 999mVDC (5.0 to 99.9%rh)
Operation ambient	0 to 50°C less than 85%rh (no condensing)
Power requirements	12VDC (exclusive AC adapter is attached) * AC adapter primary side: 100 to 240VAC 50/60Hz 0.3A, Secondary side: 12VDC 1A
Dimensions and weight	463(w) x 213(H) x 65(D)mm approx. 3.5kg

Accessories	AC adapter 4 pcs. of fittings
Options	Alarm functions (upper/lower limits) * Buzzer and rotating warning light can connect with. 2 pcs. of hanging hook