

Cat.No.8092-50

Temperature/humidity Indicator Model SK-M350-TRH



Model

SK-M350-TRH

Digital indicator which displays temperature and humidity simultaneously with LED (height of character: 57mm) Input: 0 to 1VDC
Angle of display panel is changeable.
Temperature/humidity transmitter SK-RHC-V (0 to 1V) can connect with.

Features

- * Digital indicator which displays temperature and humidity simultaneously with LED (height of character: 57mm)
- * Angle of display panel is changeable.
- * Input: 0 to 1VDC
- * Temperature/humidity transmitter Model SK-RHC-V (0 to 1V) can connect with this indicator (built-in the power supply for SK-RHC-V)
- * Alarm function (upper/lower limits) is available at option.
 - * Buzzer and rotating warning light can connect with this indicator.

Specifications

Display	7 segment LED height of character: approx. 57mm
Display range	Temperature: -15.0 to 65.0°C Humidity : 5.0 to 99.9%rh Display accuracy: $\pm(0.3 + 1\text{digit})^\circ\text{C}/\%rh$
Input	Temperature: -150 to 650mVDC (-15.0 to 65.0°C) Humidity: 50 to 999mVDC (5.0 to 99.9%rh)
Operation ambient	0 to 50°C less than 85%rh (no condensing)
Power requirement	12VDC (exclusive AC adapter is attached) * AC adapter primary side: 100 to 240VAC 50/60Hz 0.3A, Secondary side: 12VDC 1A
Dimensions & weight	360(w) x 202(H) x 85(D)mm approx. 3.7kg

Accessories	AC adapter
Options	Alarm functions (upper/lower limits) * Buzzer and rotating warning light can connect with.