



HRS-150D-ZXY Fully Automatic Rockwell Hardness Tester

Product description:

HRS-150D-ZXY Fully Automatic Rockwell Hardness Tester



(http://www.hssdgroup.com/PRODUCT/Electronic_Universal_Testing_machine/PR000011pw_Temperture_Standard/570/HRC)DUCT/ImpactTesting_Machine/360mm/PRODUCT/Hydrauli

Share With:

We're here to help:
Easy ways to get the answers you need.

Send E-mail (mailto:Louis@hssdtest.com)

Chat Now (skype:sales02@hssdtest.com?chat)

PRODUCT DETAILS

PRODUCT VIDEO

Features

1. The main hardness tester can be divided from automatic system and it can be used for testing independently.
2. Just like build with blocks, they can be upgraded according to requirement.
3. Specimen will be raised up automatically (without height limited)
4. Automatically load the initial test force
5. Automatically load the main test force
6. Automatically measure the hardness values
7. May multi-point, multi-parts test hardness value, series test, for example, automatically measure the end quenched curves for 6 pcs end quenched specimens
8. Automatically hardness exchange according to Chinese standard/ASTM
9. Automatically alarm the unqualified hardness value
10. The hardness test data will be stored forever for inquiry database
11. Automatically make the inspection report subjected by the client

Main Technical Specifications

Composition	Single Hardness Tester + Software + Z axis+X axis +Y axis motor+ Computer
Special Characteristics	Automatically accomplish the hardness testing of optional multi-points on the plane
Application	Apply to repeatedly test large quantity of specimens
Initial Test Force	10kgf(98.07N)
Test Force	60kgf(588N), 100kgf(980N), 150kgf(1471N)
Dwelling Time	0~60s
Rockwell Scales	HRA, HRB, HRC, HRD, HRE, HRF, HRG, HRH, HRK
Carry Out Standard	Chinese Standard GB/T230.1, GB/T230.2, JJG112 Inspection Rule, ASTM Standard
Max Height of Specimen	175mm, Added Height: 400mm
Distance between Indenter to outer wall	160mm
Specimen Rising Speed	3mm/s
Hardness Test Range	HRA:20-88, HRB:20-100, HRC:20-70, HRD:40-77, HRF: 60-100, HRG : 30-94, HRH : 80-100, HRK : 40-100
Specimen Rising Up	Automatically
Apply Initial Test Force	Automatically
Apply Main Test Force	Automatically
Specimen moving in X or Y Axis	Automatically Move
Moving Precision in X or Y Axis	0.003mm
Travels in X or Y Axis Direction	100mm
Hardness Value Display	Automatically
Hardness Value Exchange	Automatically
Hardness Values Output	Built-in Printer, RS232 Interface, Normal Printer
Hardness Statistic and Analysis	With
Hardness Test Database Inquiry	With
User's Stipulated Inspection Report	Automatically Form
Exchange Scales	Superficial Rockwell, Brinell, Vickers
Readout Hardness Value	Large Digital Display Screen
Overall Dimension (mm)	520x240x720mm
Power Supply	AC220V
Net Weight of Main Tester	About 65kg



Jinan Hensgrand Instrument Co., Ltd.

+86-15910081986

+86-15910081986

Louis@hssdtest.com (mailto: Louis@hssdtest.com)

4915,West jingshi Road,jinan 250012,PR CHINA.

CLASSIFICATION

Electronic Universal Testing Machine (http://www.hssdgroup.com/PRODUCT/Electronic_Universal_Testing_Machine/)

Hydraulic Universal Testing Machine (http://www.hssdgroup.com/PRODUCT/Hydraulic_Universal_Testing_Machine/)

Compression Tester (http://www.hssdgroup.com/PRODUCT/Compression_Tester/)

Impact Testing Machine (http://www.hssdgroup.com/PRODUCT/Impact_Testing_Machine/)

High And Low Temperature Chamber (http://www.hssdgroup.com/PRODUCT/Low_Temperature_Chamber/)

Specimen Making Machine (http://www.hssdgroup.com/PRODUCT/Broaching_Machine/)

Torsion Testing Machine (http://www.hssdgroup.com/PRODUCT/Torsion_Testing_Machine/)

WELCOME MY COMPANY

Welcome your arrival, we will use the best
quality service to provide you with the help!

search



We respect your privacy