KOPPACE



KOPPACE 17X-108X 16MP Full HD 1080P HDMI HD Industry Microscope for Phone PCB Repair Microscope 13.3 inch display screen

KP-F1660

Variable ratio:1:6.5
Eyepiece:0.5X
Zoom Objective:0.7X-4.5X
Optical digital amplification:17X-108X
Working distance:100mm

Description

KP-F1660	
LCD	13.3 inch HDMI HD Monitor
Eyepiece	0.5X
Zoom Objective	0.7X-4.5X
Optical digital amplification	17X-108X
Working distance	100mm
Rise and fall range	275mm
Focusing range	60mm
Base Plate size	370X250X16mm
Bracket diameter	50mm
Output Interface	HDMI,USB
Sensor	sensor 1/2.3 inch
Image resolution	4608*3456 (for TF Card),1920x1080(for TF Card),
Video recorder	1920*1080 @ 60fps

Pixel	16 million pixels
Pixel Size	1.33μm×1.33μm
Frame rate	60fps
Brightness control	Auto/manual
White Balance	manual operation,automatic
Color	R/G/B adjustable
Image freezing	Support
OSD	Support
Cross cursor	Support multi-color, size adjustable
Transverse and vertical line	Support multi-color,4 pcs of transverse lines/vertical lines,movable
TF card interface	Maximum support 64G
Lens	C/CS
USB interface	Usb2.0
Power supply	DC-12V/1A
LED ring light	Inside diameter size 60mm,The input voltage AC90-240V,The output power 4.5w, Light color white,Lamp bead 56

Packing List:

1、0.7X-4.5X zoom lens*1

2、Focus rack *1

3、Pillar stand and Base Plate *1

4、LED ring light *1

5、16 MP microscope camera *1

6、HDMI high definition line *1

7、USB data line *1

8、The camera power adapter *1

9、CD drive *1

10、Remote control *1

11、13.3 inch display screen *1

Note:
1,This product is mainly HDMI output,USB connected computer can only display images,The monitor can be displayed simultaneously with the connected computer, but the parameters cannot be adjusted when connected to the computer To adjust the parameters, you need to connect the monitor to adjust.
2,Remote control can not be used when connecting computer;using remote control to adjust parameters needs to be in HDMI connected monitor state.