



KOPPACE 3.5X-180X Trinocular Stereo Mobile Phone Repair Microscope 2 Million Pixels Microscope Camera 13.3 inch Display

KP-G400

monitor:13.3 inches
Optical Enlargement:3.5X-180X
Eyepiece:High eyespots wide-field eyepiece WF10X/20,WF20X/10
Working Distance:30mm-165mm
Objective lens 0.7X-4.5X
LED light source:LED Qty 144
Camera eyepiece interface:Dedicated interface 0.5X CTV
Auxiliary lens:0.5X/165mm,2X/30mm,1X oil proof mirror

Description

Model	KP-G400
Monitor	13.3 inches
Optical Enlargement	3.5X-180X
Eyepiece	High eyespots wide-field eyepiece WF10X/20,WF20X/10
Objective lens	0.7X-4.5X
Viewing Head	Trinocular stereomicroscope view head inclined at 45°. The pupil distance adjusting range 54mm-76mm
Stage into the circular plate	95mm Black and white board
Working Distance	30mm-165mm
Focusing bracket	Focusing handwheel tightness is adjustable, lifting range 50mm
Base Plate size	200X255X22mm
LED light source	LED Qty 144,Internal diameter size 64mm,Diameter size 94mm,Input voltage AC90—240V,Maximum output power 4.5W,Voltage 12V0.5A
Camera eyepiece interface	Dedicated interface 0.5X CTV
Auxiliary lens	0.5X/165mm,2X/30mm,1X oil proof mirror
Image specification	1920x1080
Frame rate	60 frame/second
Optical size	1/2 inches
Pixel size	2.75x2.75um
Color adjustment	R, G, and B are independent and adjustable

White balance regulation	Single key setting/manual setting
Exposure adjustment	Automatic mode/manual mode
Contrast adjustment	Manual setting
Suppression of strong light mode	3 level
Edge enhancement pattern	3 level
Cross function	Superposition or cancellation
Lens interface	C interface
Power Supply	5V-12V
Working temperature	0-70 degrees centigrade

Packing List:

- 1、Eyepiece WF10X/20 one pair
- 2、Eyepiece WF20X/10 one pair
- 3、Focus rack *1
- 4. Eye guards one pair
- 5、0.7X-4.5X Trinocular zoom objective *1
- 6、144 LED ring light *1
- 7、Pillar stand and Base Plate *1
- 8, Dust cover *1
- 9, 0.5X Auxiliary lens *1
- 10、2X Auxiliary lens *1
- 11、1X oil proof mirror *1
- 12、13.3" monitor *1
- 13、2 MP Microscope Camera *1
- 14、HDMI high definition line*1
- 15. The camera power adapter *1
- 16、Monitor Hanging Pole *1

Note:

This product cannot be photographed.