

THE ASIA'S  
TECHNOLOGY LEADER

A SINGLE-SOURCE SUPPLIER OF STRAPPING MACHINE

# THE ASIA'S TECHNOLOGY LEADER

A SINGLE-SOURCE SUPPLIER OF STRAPPING MACHINE



[Home](#) > [PRODUCTS](#) > [Automatic Strapping Machines](#) > TP-702S Mercury (stainless steel frame SUS304)

## PRODUCTS

- [Strapping Tools](#)
- [Semi-Auto Strapping Machines](#)
- [Automatic Strapping Machines](#)
- [Fully Automatic Strapping Machines](#)
- [Corrugated Strapping Machines](#)
- [Print Media Strapping Machines](#)

## TP-702S Mercury (stainless steel frame SUS304)



TP-702S is a world-class high speed automatic strapping machine with stainless steel frame (SUS 304). It is ideal for moist working environment, such as meat, seafood, poultry, and agricultural processing plants.

[? INQUIRY](#)

### Features

- Robust & compact mechanical strapping head
- High speed up to 65 straps per minute
- Free access to strap guides (*patents registered*)
- Waist-high auto strap feeding
- Waist-high quick coil change (*patents registered*)
- Turnable operating control panel
- Auto strap ejector
- Dispenser release switch
- Sensor controlled heater
- Low voltage
- Strap end ejector
- Front foot bar switch
- Adjustable table height between 820 mm and 920 mm

### Options

- Photo-eye switch
- Rear foot bar switch
- Foot pedal switch
- Lower adjustable table height (770-820 mm)
- Selected parts in stainless steel
- Stainless steel frame SUS 304

### Green Tech

#### Technical Data

Capacity	Up to 65 cycles/minute (TP-702S-59) Up to 60 cycles/minute (TP-702S-12)
Strap Width	5 mm, 6 mm, or 9 mm (TP-702S-59) 12 mm (TP-702S-12)
Tension Range	1 to 32 kg (TP-702S-59) 1 to 55 kg (TP-702S-12) (Higher tension is on request)
Weight	158 kg (TP-702S-59) 167 kg (TP-702S-12)
Electrical Requirements	110V, 220V, 230V, 240V 50/60Hz 1PH

**ALL PRODUCTS ARE WELL MADE BY OUR ISO 9001 CERTIFIED FACTORY IN  
TAIWAN, WITH PRIDE.**