

PRODUCTS

- Strapping Tools
- Semi-Auto Strapping Machines
- Automatic Strapping Machines
- Fully Automatic Strapping Machines
- Corrugated Strapping Machines
- Print Media Strapping Machines



DISTRIBUTOR SITE	EN/中文/JP ▼	Q	Search				
PRODUCTS	INDUSTRY SOLUTIONS						
ABOUT US	NEWS		FAQ				

TP-702B Mercury Transit



Features

- Robust & compact mechanical strapping head
- · Waist-high auto strap feeding
- Free access to strap guides (patents registered)
- Electronic tension control
- Auto strap ejector
- Hinged top plates
- Multiple strap function for single, double, continuous strapping, or transit mode
- Variable conveyor speed between 10 and 60 meters/minute
- Up and down stream interlock with complete plug connection
- Easy bundle flow direction change
- · Good to strap small package with minimum size 120 mm in width and 10 mm in height
- Adjustable table height between 800 mm and 900 mm

Options

- Siemens PLC
- · Light tower with low strap sensor
- · Energy saving transit with auto sleep mode
- · Strapping in the center of the bundle
- Extension belt-driven table of 200 mm on upstream and downstream sides
- Lower adjustable table height (750 mm 900 mm)

Green Tech



р	ISTRIBUTOR SITE	EN/中文/JP▼	Q	Search
J	PRODUCTS	INDUSTRY SOLUTIONS		
	ABOUT US	NEWS		FAQ

Technical Data

Strap Width	5 mm, 6 mm, 9 mm or 12 mm		
Tension Range	1-32 kg (for 5 mm, 6 mm, 9 mm) 1-55 kg (for 12 mm)		
Capacity	Up to 40 packages/minute (Cycle speed up to 65 cycles/minute)		
Weight	225 kg		
Electrical Requirements	110V, 220V, 230V, 240V 50/60Hz 1PH 220V, 380V, 400V, 415V 50/60Hz 3PH		

Video



ALL PRODUCTS ARE WELL MADE BY OUR ISO 9001 CERTIFIED FACTORY IN TAIWAN, WITH PRIDE.

☆ 15F-1, NO. 17, SEC. 1, CHENGDE ROAD, TAIPEI 103, TAIWAN ⊠ transpak@tran