



MPS-3000XP series

The multi-channel DC power supply has no problem solution, high-level and high stability, and has over-voltage, redundant protection function, provides serial and parallel working mode, the resolution is up to 1mV / 1mA.

Features

- Three channels display voltage and current at the same time, and can be adjusted
- Intelligent temperature control fan to reduce noise
- Choice of series-parallel or synchronous mode
- Low ripple and noise
- Software monitoring and correction can be done via computer
- Remote measurement function (SENSE) to compensate for voltage drop on the line
- Timing output time (0 ~ 99999.9 seconds)
- Output has switch control
- 40 sets of setting data can be saved and quickly recalled

model		MPS-3033XP	MPS-3063XP	MPS-6033XP
Rated output	Voltage	0 ~ 31V * 3	0 ~ 31V * 3	0 ~ 61V * 3
	Electric current	0 ~ 3A * 3	0 ~ 6A * 3	0 ~ 3A * 3
Load regulation	Voltage	≤0.01% + 3mV		
	Electric current	≤0.01% + 3mA		
Power regulation	Voltage	≤0.01% + 3mV		
	Electric current	≤0.01% + 3mA		
Set resolution	Voltage	1mV		
	Electric current	1mA		
Readback resolution	Voltage	1mV		
	Electric current	1mA		
Set accuracy	Voltage	≤0.03% + 10mV		
	Electric current	≤0.1% + 5mA	≤0.1% + 8mA	≤0.1% + 5mA
Readback accuracy	Voltage	≤0.03% + 10mV		
	Electric current	≤0.1% + 5mA	≤0.1% + 8mA	≤0.1% + 5mA

Ripple and noise	Voltage rms	≤2mVrms		
	Electric current	≤5mArms		
Series and parallel setpoint accuracy	Voltage	≤0.02% + 10mV	≤0.02% + 10mV	≤0.02% + 5mV
	Electric current	≤0.1% + 30mA		
memory	Store / Call	40 groups		
	Features	Timing off output		
Timer	time setting	0.1s ~ 99999.9s		
	Resolution	0.1s		
Operating temperature		0 ~ 40 ° C		
Bare metal size	mm	255 * 110 * 380	255 * 110 * 380	255 * 110 * 380
Packing size	mm	325 * 210 * 475	325 * 210 * 475	325 * 210 * 475
net weight	kg	11	11	8.5
Gross weight	kg	13	13	10