## KERN FKB8K0.1



High-resolution bench scale with large weighing range and robust stainless steel weighing



Measuring system	
Adjustment options:	External calibration
Linearity:	300 mg
Readability [d]:	100 mg
Recommended adjusting weight:	5 kg (F1); 2 kg (F1); 1 kg (F1)
Repeatability:	100 mg
Resolution:	80000
Stabilisation time under laboratory conditions:	2 s
Warm up time:	2 h
Weighing capacity [Max]:	8 kg
Weighing system:	Strain gauge
Weighing units:	ozt g lb dwt oz gn kg

Display digit height (large):	2,500 cm
Counting	
Counting resolution:	80000
Mininum piece weight at piece	100 mg

counting (Laboratory: Mininum piece weight at piece 1 g

Display

counting (Normal):

Functions		
Counting function:	yes	
Percentage determination:	yes	
PRE-TARE function:	yes	
Standby function:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C

Power supply	
Battery:	6x1.5 V AA
Charging time:	10 h
Input voltage:	100 V - 240V AC 50/60Hz 0.3A
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH AUS UK US
Operating time:	80 h
Operating time (Backlight off):	90 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional - intern

DAkkS Certificate:	963-128
Category	
Brand:	KERN
Category:	Balances
Product Group:	Bench scale

Services (optional)

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	470 x 470 x 190 mm
Gross weight:	7,500 kg
Net weight:	6,500 kg
Shipping method:	Parcel service

Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	350 x 390 x 120 mm
Dimensions of weighing plate (WxDxH):	340 x 240 x 21 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Weighing surface (WxD):	340 x 240 mm


## KERN FKB8K0.1



High-resolution bench scale with large weighing range and robust stainless steel weighing plate

## Piktogramme

STANDARD



**OPTION** 



**FACTORY** 

