

Rubber Compression Set Tester GT-KB22

Product Introduction

Application:

Rubber Compression Set Tester is used especially to test the static compression for rubber.

Standards:

CNS-3560, 10487; JIS-K6301; ASTM D395 Method B

Dimensions

External Dimensions:	
200x120x100mm(LxWxH)	
Package Dimensions:	
310x220x230mm(LxWxH)	
Gross Weight:	
30kg	
Net Weight:	
12kg	

Feature

Place one standard specimen between parallel flat plates, revolve the screws then compress it a certain range of percentage and then put into the oven under the specified temperature for a certain time period then take it off cooling for 30 minutes to measure its thickness for calculating its permanent deformation rate.

Key Specifications

Model	GT-KB22	
Specimen rubber	Diameter: 28.68mm, Thickness: 12.7mm	
Foam plastic	50 x 50 x 25mm	
Material	Stainless	
Spacer rings thickness	4.5 mm, 5mm, 7.6mm, 8.9mm, 9.5mm, 10.2mm, 12.5 mm	
Dimensions(L x W x H)	20 x 12 x 10cm	
Weight	12 kg	
Standards	CNS-3560, 10487; JIS-K6301; ASTM D395 Method B, GB/T 7759, GB/T 6669; ISO 815, ISO 1856;	

Standards	10pcs	4.5mm Spacer rings
	10pcs	9.5mm Spacer rings
Option accessories	Optional	5mm or 7.6mm or 8.9mm or 10.2mm or 12.5 mm of Spacer rings
	Optional	GT-KD01 Aging Oven