

Precision LCR Meter

AT-120



Product Features

- 4.3 “ LCD Display
- System provides 50 Hz—200 kHz(37 points)
- Output impedance 30 Ω, 100 Ω
- Basic Accuracy 0.1%
- Test Volt. Normal: 0.1V、0.3V、 1V
- Software upgrade by USB HOST

Test Item

| Z|, |Y|, C, L, X, B, R, G, D, Q, θ

RANGE	
Z , R, X	0.01m Ω — 99.999 MΩ
Y , G, B	0.0001μS — 99.999 S
C	0.0001 pF — 9.9999 F
L	0.0001 μH — 999.99 H
D	0.0001 — 9.9999
Q	0.0001 — 99999
θ	-179.99 °— 179.99 °

Specifications

Temp. Humidity		0℃—40℃, £90%RH
Power	Volt.	110V ±10% Or 220 ±10%
	Freq	47.5Hz—63Hz
Power consumption		≤ 30VA
Size (W×H×D)		

Weight	About 2.5kg
--------	-------------

Comprehensive	
Test Freq.	50Hz~200kHz, (37 points)
Basic Accuracy	0.05%
Equivalent Circuit	Series, Parallel
Comparator	Upper and Lower test limits in units and percentage
Test mode	Auto, Continued, Manual
Touch mode	Internal, Manual, External
Test speed ($\geq 1\text{kHz}$)	Fast: 40t/sec, Medium: 11t/sec, Slow: 3t/sec
average number	1—255
Delay Time	0—60s, 1ms step
Calibration	open/ short / load
Test configuration	Five end
Display mode	Δ , $\Delta\%$, V/I (Voltage / current monitoring)
LCD	4.3'LCD
Test signal	
Freq.	50 Hz—200 kHz
Output impedance	30 Ω , 100 Ω (Select)
Test Volt.	Normal: 0.1V、0.3V、1V Accuracy: 10%
Memory	100(Internal) , 500 (External)
Interface	RS232C、HANDLER、USB HOST, (OPTION GPIB)

Purchase information

AT-120 Precision LCR Meter

Accessories

AT26001A	Four wire Kelvin cable
AT26004-1	Four wire Kelvin cable
AT26010A	Gold plated circuit / Short board
AT26009B	SMD test clamp
AT26008A	SMD test box
AT10201	Software