



CSA Series Signal Analyzer

Datasheet



Saluki Technology Inc.

The document applies to the signal analyzer of the following models:

- CSA2007 signal analyzer (100 kHz - 7.5 GHz)
- CSA2013 signal analyzer (100 kHz - 13.5 GHz)
- CSA2026 signal analyzer (100 kHz - 26.5 GHz)

Document No.

CSA2026-02-01

Version

Rev01 2021.07

Saluki Technology

Document Authorization

The information contained in this document is subject to change without notice. The power to interpret the contents of and terms used in this document rests with Saluki.

Saluki Tech owns the copyright of this document which should not be modified or tampered by any organization or individual, or reproduced or transmitted for the purpose of making profit without its prior permission, otherwise Saluki will reserve the right to investigate and affix legal liability of infringement.

Product Quality Assurance

The warranty period of the product is three years from the date of delivery. The instrument manufacturer will repair or replace damaged parts according to the actual situation within the warranty period.

Product Quality Certificate

The product meets the indicator requirements of the document at the time of delivery. Calibration and measurement are completed by the measuring organization with qualifications specified by the state, and relevant data are provided for reference.

Quality/Settings Management

Research, development, manufacturing and testing of the product comply with the requirements of the quality and environmental management system.

Contact

Service Tel: 886. 909 602 109
Website: www.salukitec.com
Email: sales@salukitec.com
Address: No. 367 Fuxing N Road, Taipei 105, Taiwan (R.O.C.)

Contents

Definitions and conditions.....	4
Frequency and Time Specifications.....	5
Amplitude Accuracy and Range Specifications.....	7
Dynamic Range Specifications.....	9
General Specifications.....	12
Inputs and Outputs.....	12
I/Q Analyzer.....	13
System Requirements.....	14

Definitions and conditions

Temperatures referred to in this document are defined as follows:

–Full temperature range = Individual module temperature of 5 to 68 °C, as reported by the module, and environment temperature of 0 to 55 °C.

–Controlled temperature range = Individual module temperature of 25 to 40 °C, as reported by the module, and environment temperature of 20 to 30 °C.

Specifications describe the warranted performance of calibrated instruments. Specifications data under the following conditions:

- It is within its calibration cycle
- Under auto couple control, except when Auto Sweep Time Rules = Accy
- The analyzer has been stored at an ambient temperature within the allowed operating range for at least two hours before being turned on; if it had previously been stored at a temperature range inside the allowed storage range, but outside the allowed operating range
- The analyzer has been turned on at least 30 minutes with Auto Align set to normal, or, if Auto Align is set to off or partial, alignments must have been run recently enough to prevent an Alert message; if the Alert condition is changed from Time and Temperature to one of the disabled duration choices, the analyzer may fail to meet specifications without informing the user

95th percentile values indicate the breadth of the population (approx. 2σ) of performance tolerances expected to be met in 95 percent of the cases with a 95 percent confidence, for any ambient temperature in the range of 20 to 30 °C. In addition to the statistical observations of a sample of instruments, these values include the effects of the uncertainties of external calibration references. These values are not warranted.

Typical describes additional product performance information that is not covered by the product warranty. It is performance beyond specifications that 80 percent of the units exhibit with a 95 percent confidence level over the temperature range 20 to 30 °C. Typical performance does not include measurement uncertainty.

Nominal values indicate expected performance, or describe product performance that is useful in the application of the product, but are not covered by the product warranty. Data represented in this document are Nominal unless otherwise noted.

Frequency and Time Specifications

Frequency range		
Frequency range		10Hz to 7.5 GHz
		10Hz to 13.5 GHz
		10Hz to 26.5 GHz
Band	LO multiple (N)	
0	1	100kHz to 3.05GHz
1	2	2.95GHz to 7.55GHz
2	2	7.45GHz to 9.25GHz
3	2	9.15GHz to 11.05GHz
4	2	10.95GHz to 12.75GHz
5	4	12.65GHz to 14.55GHz
6	4	14.45GHz to 16.55GHz
7	4	16.45GHz to 18.55GHz
8	4	18.45GHz to 20.55GHz
9	4	20.45GHz to 24.55GHz
10	4	24.45GHz to 26.5GHz
Frequency reference		
Accuracy	$\pm[(\text{time since last adjustment} \times \text{aging rate}) + \text{temperature stability} + \text{calibration accuracy}]$	
Aging rate	$\pm 3 \times 10^{-7}$ / year (First year)	
Temperature stability		
20 to 30°C	$\pm 3 \times 10^{-8}$	
Full temperature range	$\pm 3 \times 10^{-8}$	
Achievable initial calibration accuracy	$\pm 8 \times 10^{-8}$	
Example frequency reference accuracy	$= \pm (3 \times 10^{-7} + 3 \times 10^{-8} + 8 \times 10^{-8})$	
1 year after last adjustment	$= \pm 4.1 \times 10^{-7}$	
Residual FM	$\leq 1\text{Hz p-p in 20 ms nominal}$	
Frequency readout accuracy (start, stop, center, marker)		
$\pm (\text{marker frequency} \times \text{frequency reference accuracy} + 0.25 \% \times \text{span} + 5 \% \times \text{RBW} + 2\text{Hz} + 0.5 \times \text{horizontal resolution})$		
Marker frequency counter		
Accuracy	$\pm (\text{marker frequency} \times \text{frequency reference accuracy} + 0.100\text{Hz})$	
Delta counter accuracy	$\pm (\text{delta frequency} \times \text{frequency reference accuracy} + 0.141\text{Hz})$	
Counter resolution	0.001Hz	
Frequency span (FFT and swept mode)		
Range	0Hz(zero span), 10Hz to maximum frequency of instrument	
Resolution	2Hz	
Accuracy		
Swept	$\pm (0.25\% \times \text{span} + \text{horizontal resolution})$	
FFT	$\pm (0.10\% \times \text{span} + \text{horizontal resolution})$	

Sweep time and triggering

Range	Span = 0Hz	1 μ s to 6000s
	Span $\geq$ 10Hz	1ms to 4000s
Accuracy	Span $\geq$ 10Hz, swept	$\pm 0.01\%$ nominal
	Span $\geq$ 10Hz, FFT	$\pm 40\%$ nominal
	Span = 0Hz	$\pm 1\%$ nominal
Trigger	Free run, video, external, RF burst, periodic timer	
Trigger delay	Span = 0 Hz or FFT	-150 to +500ms
	Span $\geq$ 10 Hz, swept	1 μ s to 500ms
	Resolution	0.1 μ s

Time gating

Gate methods	Gated LO; gated video; gated FFT
Gate length range (except method = FFT)	100.0ns to 5.0s
Gate delay range	0 to 100.0s
Gate delay jitter	33.3ns p-p nominal

Sweep (trace) point range

All spans	1 to 40001
-----------	------------

Resolution bandwidth (RBW)

Range (-3.01 dB bandwidth)	1 Hz to 3 MHz (10 % steps), 4, 5, 6, 8 MHz	
Bandwidth accuracy (power)	1Hz to 750kHz	$\pm 1.0\%(\pm 0.044\text{dB})$ nominal
	820kHz to 1.2MHz	$\pm 2.0\%(\pm 0.088\text{dB})$ nominal
	1.3 to 2.0MHz	$\pm 0.13\text{dB}$ nominal
	2.2to 3MHz	$\pm 0.22\text{dB}$ nominal
	4 to 8MHz	$\pm 0.32\text{dB}$ nominal
Bandwidth accuracy (-3.01 dB)	1Hz to 1.3MHz	$\pm 2\%$ nominal

RBW range

Selectivity (-60 dB/-3 dB)	4.1:1 nominal
----------------------------	---------------

Analysis bandwidth

Maximum bandwidth	25MHz (40MHz Option)
-------------------	----------------------

Video bandwidth (VBW)

Range	1 Hz to 3 MHz (10 % steps), 4, 5, 6, 8 MHz, and wide open (labeled 50 MHz)
Accuracy	$\pm 6\%$ nominal

Measurement speed

Local measurement and display update rate	11ms (90/s) nominal
Remote measurement and LAN transfer rate	6ms (167/s) nominal
Marker peak search	5ms nominal
Center frequency tune and transfer	22ms nominal
Measurement/mode switching	75ms nominal

Amplitude Accuracy and Range Specifications

Amplitude range

Measurement range

Preamp off

Displayed average noise level (DANL) to +27dBm

Input attenuator range

0 to 70 dB in 2dB steps

Maximum safe input level

Average total power

+27dBm(0.5W)

Input attenuation $\geq$ 10dB, preamp off

+27dBm(0.5W)

Input attenuation $\geq$ 20dB, preamp on

Peak pulse power

+47dBm(50W)

< 10 μ s pulse width, < 1% duty cycle, and input attenuation $\geq$ 30dB

DC volts

AC coupled

 ± 16 Vdc

Display range

Log scale

0.1 to 1dB/division in 0.1dB steps

1 to 20dB/division in 1dB steps (10 display divisions)

Linear scale

10 divisions

Scale units

dBm , dBmV , dB μ V , dBmA , dB μ A , V , W , A

Frequency response

Specification

95%($\approx 2\sigma$)

(10dB input attenuation, 20 to 30°C, σ = nominal standard deviation)

9kHz to 10MHz

 ± 0.50 dB

 ± 0.4 dB

10MHz to 3GHz

 ± 0.65 dB

 ± 0.5 dB

3 to 13.6GHz

 ± 1.30 dB

 ± 0.8 dB

13.6 to 19.3GHz

 ± 1.50 dB

 ± 1.0 dB

19.3 to 24.2GHz

 ± 2.20 dB

 ± 1.3 dB

24.2 to 26.5GHz

 ± 2.50 dB

 ± 1.3 dB

Preamp on

100kHz to 10MHz

 ± 0.5 dB

10MHz to 3GHz

 ± 1.0 dB

3 to 7.5GHz

 ± 1.2 dB

7.5 to 13.6GHz

 ± 1.0 dB

13.6 to 21GHz

 ± 1.2 dB

21 to 24.2GHz

 ± 1.8 dB

24.2 to 26.5GHz

 ± 2.4 dB

Input attenuation switching uncertainty

Specifications

Additional information

Attenuation > 2dB, preamp off

50MHz (reference frequency)

 ± 0.3 dB

 ± 0.15 dB typical

Relative to 10 dB

100kHz to 3.0GHz

 ± 0.30 dB nominal

(reference setting)

3.0 to 7.5GHz

 ± 0.50 dB nominal

7.5 to 26.5GHz		±0.70dB nominal
Total absolute amplitude accuracy		
(10dB attenuation, 20 to 30°C, 1Hz ≤ RBW ≤ 1MHz, input signal -10 to -50dBm, all settings auto-coupled except Auto Swp Time = Accy, any reference level, any scale, σ = nominal standard deviation)		
At 50MHz	±0.40dB	
At all frequencies	±(0.40dB + frequency response)	
100kHz to 3GHz	±0.60dB(95%≈2σ)	
Preamp on	±(0.36dB + frequency response)	
	(95%)	
Input voltage standing wave ratio (VSWR) (0dB attenuation)		
10MHz to 26.5GHz	< 2.0 nominal	
Resolution bandwidth switching uncertainty (referenced to 30 kHz RBW)		
1Hz to 3MHz RBW	±0.15dB	
4 , 5 , 6 , 8MHz RBW	±1.0dB	
Reference level		
Range		
Log scale	-170 to +23dBm in 0.01dB steps	
Linear scale	Same as log (707pV to 3.16V)	
Accuracy	0dB	
Display scale switching uncertainty		
Switching between linear and log	0dB	
Log scale/div switching	0dB	
Display scale fidelity		
-80dBm ≤ input mixer level < -10dBm	±0.15dB total	
Trace detectors		
Normal, peak, sample, negative peak, log power average, RMS average, and voltage average		
Preamplifier		
Frequency range	100kHz to 26.5GHz	
Gain	100kHz to 26.5GHz	+20dB nominal
Noise figure	10MHz to 26.5GHz	DANL+176.24dB nominal

Dynamic Range Specifications

1dB gain compression (two-tone)

		Total power at input mixer
Preamp off	10MHz to 7.5GHz	+6dBm nominal
	7.5 to 26.5GHz	+4dBm nominal
Preamp on	10MHz to 7.5GHz	-15dBm nominal
	7.5 to 26.5GHz	-19dBm nominal

Displayed average noise level (DANL) (Input terminated, sample or average detector, averaging type = Log, 0dB input attenuation, IF Gain = High, 20 to 30°C) Parentheses indicate typical performance

	Preamplifier OFF	Preamplifier ON
100kHz to 1MHz	(-125)dBm	
1 to 10MHz	-144,(-148)dBm	-154,(-158)dBm
10MHz to 1.5GHz	-148,(-150)dBm	-160,(-163)dBm
1.5 to 4.5GHz	-146,(-149)dBm	-160,(-163)dBm
4.5 to 7GHz	-141,(-145)dBm	-157,(-161)dBm
7 to 9.5GHz	-144,(-147)dBm	-158,(-160)dBm
9.5 to 13GHz	-136,(-140)dBm	-156,(-160)dBm
13 to 14.5GHz	-142,(-145)dBm	-158,(-161)dBm
14.5 to 19.3GHz	-132,(-138)dBm	-153,(-157)dBm
19.3 to 23GHz	-134,(-139)dBm	-152,(-157)dBm
23 to 24GHz	-132,(-137)dBm	-150,(-155)dBm
24 to 26.5GHz	-128,(-133)dBm	-144,(-149)dBm

Spurious responses

Residual response (Input terminated and 0dB attenuation)	200kHz to 26.5GHz(swept)	-90dBm	
	Zero span or FFT or other frequencies	-100dBm nominal	
Image responses (First mixer)	Tuned frequency (f)	Mixer level	Response
	10MHz to 26.5GHz	-10dBm	-70dBc(-80dBc typical)
Image responses (Second mixer)	Tuned frequency (f)	Excitation Freq	Mixer level Response
	10MHz to 20.5GHz	f+1470MHz	-10dBm -70dBc(-80dBc typical)
	20.5GHz to 26.5GHz	f-1470MHz	-10dBm -70dBc(-80dBc typical)
LO-related spurious	10MHz to 26.5GHz		-10dBm -64dB typical
Other spurious responses	Mixer level	Response	
IF feedthrough	-10dBm	-75dBc(-80dBc typical)	
First RF order (f ≥ 10 MHz from carrier)	-10dBm	-70dBc(-80dBc standard)	
High RF order (f ≥ 10 MHz from carrier)	-10dBm	-70dBc(-80dBc standard)	

Second harmonic distortion (SHI)

Source frequency	SHI(nominal)
10MHz to 3.75GHz	+50dBm
3.75 to 13.25GHz	+62dBm

Third-order intermodulation distortion (TOI)

Parentheses indicate typical performance

Preamp off	10MHz to 2GHz	+12dBm,(+16)dBm
(Two -20 dBm tones at input mixer spaced by 100 kHz, 0 dB attenuation,20 to 30 °C)	2 to 3GHz	+12dBm,(+17)dBm
	3 to 7.5GHz	+12dBm,(+16)dBm
	7.5 to 13.6GHz	+11dBm,(+15)dBm
	13.6 to 26.5GHz	+10dBm,(+14)dBm
Preamp on	10MHz to 26.5GHz	-8dBm nominal
(Two -45 dBm tones at input mixer spaced by 100 kHz, 0 dB attenuation,20 to 30 °C)		





Figure 1. Nominal dynamic range for Band 0, for second and third order distortion,10 MHz to 3



GHz

Figure 2. Nominal dynamic range, for second and third order distortion, 3 GHz to 26.5 GHz

Phase noise	Offset	Specification	Typical
Noise sidebands (20 to 30°C, CF=1 GHz)			
	100Hz		-80dBc/Hz nominal
	1kHz	-100dBc/Hz	-102dBc/Hz
	10kHz	-106dBc/Hz	-108dBc/Hz

100kHz	-108dBc/Hz	-110dBc/Hz
1MHz	-130dBc/Hz	-132dBc/Hz




Figure 3. Nominal phase noise at different center frequencies

General Specifications

Temperature range

Operating	0 to 55°C
Storage	-40 to 70°C

Environmental stress

Samples of this product have been type tested in accordance with the Saluki Technology Environmental Test Manual and verified to be robust against the environmental stresses of storage, transportation, and end-use; those stresses include, but are not limited to, temperature, humidity, shock, vibration, altitude, and power line conditions.

Power requirement

Power drawn from chassis	≤90W
--------------------------	------

Weight

Net	2.2kg(4.9 lbs)
Shipping	4.2kg(9.3 lbs)

Dimensions

Height	64mm(2.5 in)
Width	150mm(5.9 in)
Length	175mm(6.9 in)

Calibration cycle

The recommended calibration cycle is one year; calibration services are available through Saluki Technology service centers

Inputs and Outputs

RF input

Connector	2.92mm-K,50Ω nominal
-----------	----------------------

10 MHz in

Connector	SMA-K,50Ω nominal
-----------	-------------------

10 MHz out

Connector	SMA-K,50Ω nominal
-----------	-------------------

Trigger in

Connector	SMA-K,10kΩ nominal
-----------	--------------------

Trigger out

Connector	SMA-K,50Ω nominal
-----------	-------------------

Analog out

Connector	SMA-K,50Ω nominal
-----------	-------------------

I/Q Analyzer

Frequency

Frequency span

Standard instrument	10Hz to 25MHz
Option B40	10Hz to 40MHz

Resolution bandwidth (spectrum measurement)

Range

Overall	100mHz to 3MHz
Span = 1MHz	50Hz to 1MHz
Span = 10kHz	1Hz to 10kHz
Span = 100Hz	100mHz to 100Hz

Window shapes

Flat top, Uniform, Hanning, Gaussian, Blackman, Blackman-Harris, Kaiser Bessel (K-B 70 dB, K-B 90 dB and K-B 110 dB)

Analysis bandwidth

Standard instrument	10Hz to 25MHz
Option B40	10Hz to 40MHz

IF frequency response (standard 10 MHz IF path)

IF frequency response (demodulation and FFT response relative to the center frequency, 20 to 30°C)

Center frequency (GHz)	Span (MHz)	Max. error	RMS (nominal)
≤ 3.0	≤ 10	$\pm 0.40\text{dB}$	0.03dB
$3.0 < f \leq 26.5$	≤ 10		0.10dB

IF phase linearity (deviation from mean phase linearity, nominal)

Center frequency (GHz)	Span (MHz)	Peak-to-peak	RMS
≤ 3.0	≤ 10	0.5°	0.2°
$3.0 < f \leq 7.5$	≤ 10	0.5°	0.4°
$7.5 < f \leq 26.5$	≤ 10	0.5°	0.4°

Data acquisition (standard 10 MHz IF path)

Time record length	4,000,000 IQ sample pairs
Sample rate	90MSa/s
ADC resolution	14 Bits

Data acquisition (B40 IF path)

Time record length

IQ analyzer	4,000,000 IQ sample pairs
Sample rate	90MSa/s
ADC resolution	14 Bits

System Requirements

Operating system	Windows10(64 bit)
Processor speed	1.86 GHz minimum
Available memory	4 GB minimum
	8 GB recommended
Available disk space	4GB
Video	Support for DirectX 10 graphics with 128 MB graphics recommended (SuperVGA supported)
Browser	Microsoft Internet Explorer 7.0 or greater

--- End of Document ---